

## ST-1500-678 Spec Sheet

ST-1500-678	<ul style="list-style-type: none"> <li>• 1500C Continuous Operating Temperature</li> </ul>
Chamber Dimensions	<ul style="list-style-type: none"> <li>• 6”(W) x 7”(H) x 8”(D)</li> </ul>
Power	5 KW
Max. Current	30A
Voltage	208/240V Single Phase
Uniformity at 1200 °C	+/- 3°C
Max. Heating Rate	10-15°C/minute depending on load volume
Temperature Control	<ul style="list-style-type: none"> <li>• Yudian Temperature Controller</li> <li>• 1 Program, 30 segments PID Programmable</li> <li>• +/- 1 °C temperature accuracy.</li> <li>• S type Platinum Rhodium long lasting thermocouple</li> <li>• Optional Controllers:               <ul style="list-style-type: none"> <li>○ Eurotherm 2404</li> <li>○ Eurotherm 3404</li> <li>○ Eurotherm Nanodac Controller/Recorder</li> </ul> </li> </ul>
Heating Elements	U- Shaped Silicon Carbide Heating Elements
Net Weight	220 lbs
Overall Dimensions	28”(L) x 23”(W) x 40”(H)
Warranty	<ul style="list-style-type: none"> <li>• One year warranty on electronic parts</li> </ul>
Optional Items	<ul style="list-style-type: none"> <li>• Argon Purge Kit</li> <li>• Exhaust Port</li> <li>• Motor Driving Forced Exhaust Port</li> <li>• PC Data Logger (records temperature from Thermocouple to PC files).</li> <li>• UL/CSA Certified Parts in Control System</li> <li>• 3 Year Extended Warranty on all electronic parts (not including shipping)</li> <li>• 5 Year Extended Warranty on all electronic parts (not including shipping)</li> </ul>